

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 62384

September 2006

ICS 29.140.99; 31.080.99

English version

**DC or AC supplied electronic control gear
for LED modules -
Performance requirements
(IEC 62384:2006)**

Appareillages électriques alimentés
en courant continu ou alternatif
pour modules de DEL -
Exigences de performances
(CEI 62384:2006)

Gleich- oder wechselstromversorgte
elektronische Betriebsgeräte
für LED-Module -
Anforderungen an die Arbeitsweise
(IEC 62384:2006)

This European Standard was approved by CENELEC on 2006-09-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

The text of document 34C/752/FDIS, future edition 1 of IEC 62384, prepared by SC 34C, Auxiliaries for lamps, of IEC TC 34, Lamps and related equipment, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 62384 on 2006-09-01.

This standard is to be used in conjunction with EN 61347-2-13.

The following dates were fixed:

- latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2007-06-01
- latest date by which the national standards conflicting with the EN have to be withdrawn (dow) 2009-09-01

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 62384:2006 was approved by CENELEC as a European Standard without any modification.

www.Lisungroup.cc

CONTENTS

1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 General notes on tests.....	5
5 Classification.....	5
5.1 Classification according to the load.....	5
5.2 Classification according to the output voltage.....	6
5.3 Classification according to the output current.....	6
6 Marking	6
6.1 Mandatory marking	6
6.2 Optional marking	6
7 Output voltage and current	6
7.1 Starting and connecting requirements	6
7.2 Voltage and current during operation	7
7.3 Capacitive load requirement.....	7
7.4 Voltage surges during switching and operation	7
8 Total circuit power	7
9 Circuit power factor	7
10 Supply current.....	7
11 Impedance at audio-frequencies	8
12 Operational tests for abnormal conditions.....	8
13 Endurance.....	8
Annex A (normative) Tests.....	10
Annex B (informative) A guide to quoting product life and failure rate	13
Annex ZA (normative) Normative references to international publications with their corresponding European publications.....	15
Bibliography.....	14

DC OR AC SUPPLIED ELECTRONIC CONTROL GEAR FOR LED MODULES – PERFORMANCE REQUIREMENTS

1 Scope

This international standard specifies performance requirements for electronic control gear for use on d.c. supplies up to 250 V and a.c. supplies up to 1 000 V at 50 Hz or 60 Hz with an output frequency which can deviate from the supply frequency, associated with LED modules according to IEC 62031. Control gear for LED modules specified in this standard are designed to provide constant voltage or current. Deviations from the pure voltage and current types do not exclude the gear from this standard.

NOTE 1 The tests in this standard are type tests. Requirements for testing individual control gear during production are not included.

NOTE 2 Requirements for control gear which incorporate means for varying the output power are under consideration.

NOTE 3 It may be expected that control gear complying with this standard will ensure satisfactory operation between 92 % and 106 % of the rated supply voltage, taking into account the specifications of the LED module manufacturer.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61347-2-13, *Lamp controlgear – Part 2-13: Particular requirements for d.c. or a.c. supplied electronic control gear for LED modules*

IEC 62031, *LED modules for general lighting – Safety requirements* ¹

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

total circuit power

total power dissipated by control gear and LED module(s) in combination, at rated supply voltage of the control gear and at the highest rated output load.

3.2

circuit power factor

λ

ratio of the measured circuit power to the product of the supply voltage (r.m.s.) and the supply current (r.m.s.).

3.3

high audio-frequency impedance control gear

control gear the impedance of which in the frequency range 250 Hz to 2 000 Hz exceeds the values specified in Clause 11 of this standard.

4 General notes on tests

4.1 The tests according to this standard are type tests.

NOTE The requirements and tolerances permitted by this standard are based on testing of a type test sample submitted by the manufacturer for that purpose. In principle this type test sample should consist of units having characteristics typical of the manufacturer's production and be as close to the production centre point values as possible.

It may be expected with the tolerances given in the standard that products manufactured in accordance with the type test sample will comply with the standard for the majority of the production. Due to the production spread however, it is inevitable that there will sometimes be products outside the specified tolerances. For guidance of sampling plans and procedures for inspection by attributes, see IEC 60410.

4.2 For tests which are carried out with a LED module or LED modules, this (these) LED module(s) shall fulfil the following requirements:

The wattage of the LED module(s) when measured at its(their) rated voltage or rated current (d.c. and/or a.c.) shall not differ from the rated wattage by more than +6 % and -0 %.

4.3 The tests shall be carried out in the order of the clauses, unless otherwise specified.

4.4 One specimen shall be submitted to all the tests.

4.5 In general all the tests are made on each type of control gear or, where a range of similar control gear is involved for each rated wattage in the range or on a representative selection from the range as agreed with the manufacturer.

4.6 The tests shall be made under the conditions specified in Clause A.1. Since up to now data of LED modules are not published in an IEC standard, they shall be made available by the LED module manufacturer.

4.7 All control gear covered by this standard shall comply with the requirements of IEC 61347-2-13.

4.8 The tests shall be carried out with the length of the output cable of both 20 cm and 200 cm unless otherwise declared by the manufacturer.

5 Classification

5.1 Classification according to the load

a) Single value load control gear

This type of control gear is designed for use with one specific output wattage only, which may be dissipated by one or more LED modules.

b) Multiple value load control gear

This type of control gear is designed for use with one or more LED modules with a total load within the declared wattage range.

5.2 Classification according to the output voltage

- a) Control gear having a stabilised output voltage
- b) Control gear without a stabilised output voltage

5.3 Classification according to the output current

- a) Control gear having a stabilised output current
- b) Control gear without a stabilized output current

6 Marking

6.1 Mandatory marking

6.1.1 Control gear shall be clearly marked as follows:

Circuit power factor; e.g. $\lambda = 0,9$

If the power factor is less than 0,95 leading, it shall be followed by the letter "C", e.g. $\lambda = 0,9\text{ C}$.

6.1.2 In addition to the above mandatory marking, the following information shall either be given on the control gear or made available in the manufacturer's catalogue or the like:

- a) if applicable: limits of the permissible temperature range;
- b) if applicable: an indication that the control gear has a stabilised output voltage;
- c) if applicable: an indication that the control gear has a stabilised output current;
- d) if applicable: an indication that the control gear is suitable for operation with a mains supply dimmer;
- e) if applicable: an indication of the operation mode, e.g. phase control.

6.2 Optional marking

The following information may either be given on the control gear or made available in the manufacturer's catalogue or the like:

- a) total circuit power;
- b) if applicable: the symbol Z which indicates that the control gear is designed to comply with conditions for audio-frequency impedance;
- c) If applicable: a symbol which indicates that the control gear is a short-circuit proof type (the symbol is under consideration).

7 Output voltage and current

7.1 Starting and connecting requirements

After starting or connecting a LED module, the output should be within 110 % of its rated value within 2 s. Maximum current or maximum voltage shall not exceed the values given by the manufacturer. This performance is tested with the minimum rated power.

NOTE If the output voltage is a.c., 110 % is the percentage of the r.m.s. value, if d.c., 110 % is the percentage of the d.c. value.

7.2 Voltage and current during operation

For control gear having a non-stabilised output voltage, when supplied with the rated supply voltage, the output voltage shall not differ by more than $\pm 10\%$ from the rated voltage of the LED modules; for control gear having a stabilised output voltage when supplied at any supply voltage between 92 % and 106 % of the rated supply voltage, the output voltage shall not differ by more than $\pm 10\%$ from the rated voltage of the LED modules.

For control gear having a non-stabilised output current, when supplied with the rated supply voltage, the output current shall not differ by more than $\pm 10\%$ from the rated current of the LED modules; for control gear having a stabilised output current when supplied at any supply voltage between 92 % and 106 % of the rated supply voltage, the output current shall not differ by more than $\pm 10\%$ from the rated current of the LED modules.

Multiple load control gear shall be tested with both the minimum and maximum load.

7.3 Capacitive load requirement

If the LED module or any additional control unit connected to the convertor contain capacitors for control and/or driving circuitry on the modules, current pulses may be generated when connecting the LED module to the control gear. This shall not disturb the control gear overcurrent detection nor the starting process of the control gear.

For test conditions, See clause A.2. Figure A.1a describes a test circuit during the starting process of the control gear and figure A.1b describes a test circuit for connecting the load during steady state operation.

Compliance: when connecting the measurement circuit to the control gear, the detection device shall not trip.

7.4 Voltage surges during switching and operation

Voltage surges superimposed on the output voltage shall not exceed the values specified below (values under consideration).

8 Total circuit power

At rated voltage, the total circuit power shall not be more than 110 % of the value declared by the manufacturer, when the control gear is operated with LED module(s).

9 Circuit power factor

The measured circuit power factor shall not be less than the marked value by more than 0,05 when the control gear is operated on its rated wattage with LED module(s) and the whole combination is supplied with rated voltage and frequency.

10 Supply current

At rated voltage, the supply current shall not differ by more than $+10\%$ from the value marked on the control gear or declared in the manufacturer's literature, when that control gear is operated on its rated wattage with LED module(s).

11 Impedance at audio-frequencies

Control gear marked with the audio-frequency symbol Z (see subclause 6.2b)) shall be tested in accordance with Clause A.3, using the circuit in Figure A.2.

For every signal frequency between 400 Hz and 2 000 Hz, the impedance of the control gear when operated with the rated LED module load at rated voltage and frequency shall be inductive in characteristic. Its impedance in ohms shall be at least equal to the resistance of the resistor which would dissipate the same power as the LED module-control gear combination when operating at its rated voltage and frequency. The control gear impedance is measured with a signal voltage equal to 3,5 % of the rated supply voltage of the control gear.

Between 250 Hz and 400 Hz, the impedance shall be at least equal to half the minimum value required for frequencies between 400 Hz and 2 000 Hz.

NOTE Radio interference suppressors consisting of capacitors of less than 0,2 μF (total value) which may be incorporated in the control gear may be disconnected for this test.

12 Operational tests for abnormal conditions

The control gear shall not be damaged under following conditions.

a) Test without LED module(s) inserted

The control gear shall be supplied with rated voltage for 1 h without LED module(s) inserted. At the end of this test, the LED module(s) shall be connected and shall operate normally.

b) Test for reduced LED module resistance

Under consideration.

c) Tests for short-circuit proof control gear

The control gear is short-circuited for 1 h or until a protecting device opens the circuit.

After these tests and after restoration of a possible protecting device, the control gear shall function normally.

13 Endurance

13.1 The control gear shall be subjected to a temperature cycling shock test and a supply voltage switching test as follows:

a) Temperature cycling shock test

The non-energised control gear shall be stored firstly at -10°C or if the control gear is marked with a lower value, at that value for 1 h. The control gear is then moved into a cabinet having a temperature of t_c and stored for 1 h. Five such temperature cycles shall be carried out.

b) Supply voltage switching test

At rated supply voltage the control gear shall be switched on and off for 30 s. The cycling shall be repeated 200 times with no load and 800 times with maximum load conditions.

LED modules failing during this test shall be replaced immediately.

At the end of these tests the control gear shall operate an appropriate LED module or LED modules correctly for 15 min.

13.2 The control gear shall then be operated with an appropriate LED module/with appropriate LED modules at rated supply voltage and at the ambient temperature which produces t_c , until a test period of 200 h has passed. At the end of this time, and after cooling down to room temperature, the control gear shall operate an appropriate LED module/appropriate LED modules correctly for 15 min. During this test the LED module(s) is (are) placed outside the test enclosure in an ambient temperature of $(25 \pm 5)^\circ\text{C}$.

www.Lisungroup.cc

Annex A
(normative)**Tests****A.1 General requirements****A.1.1 General**

The tests are type tests. One sample shall be submitted to all the tests.

A.1.2 Ambient temperature

The tests shall be made in a draught-free room and at an ambient temperature within the range 20°C to 27°C.

A.1.3 Supply voltage and frequency**a) Test voltage and frequency**

Unless otherwise specified, the control gear to be tested shall be operated at its rated supply voltage and frequency.

When a control gear is marked for use on a range of supply voltages, or has different separate rated supply voltages, any voltage for which it is intended may be chosen as the rated voltage.

b) Stability of supply voltage and frequency

During the tests, the supply voltage and the frequency shall be maintained constant within $\pm 0,5\%$. However, during the actual measurement, the voltage shall be adjusted to within $\pm 0,2\%$ of the specified testing value.

c) Supply voltage waveform

The total harmonic content of the supply voltage shall not exceed 3 %. Harmonic content being defined as the root-mean-square (r.m.s.) summation of the individual components using the fundamental as 100%.

A.1.4 Magnetic effects

Unless otherwise specified, no magnetic object shall be allowed within 25 mm of any outer surface of the control gear under test.

A.1.5 Instrument characteristics**a) Potential circuits**

Potential circuits of instruments connected across the LED module shall not pass more than 3 % of the nominal running current of the LED module.

b) Current circuits

Instruments connected in series with the LED module shall have a sufficiently low impedance such that the voltage drop shall not exceed 2 % of the objective LED module voltage.

c) RMS measurements

Instruments shall be essentially free from errors due to waveform distortion and shall be suitable for the operating frequencies.

Care shall be taken to ensure that the earth capacitance of the instruments does not disturb the operation of the unit under test. It may be necessary to ensure that the measuring point of the circuit under test is at earth potential.

A.2 Measurement of capacitive load current (Figures A.1a and A.1b)

Figure A.1 illustrates the test circuit for the current when connecting a load.




Figure A.1a – Test circuit for current during the starting process




Figure A.1b – Test circuit for current when connecting the load during the steady state operation

Key to figures A.1a and A.1b

- U : Supply 50 Hz (60 Hz)
- S : Switch
- D.U.T. : Control gear under test
- R : Resistor which gives the nominal output current of the D.U.T.
For voltage sources: $R = U^2/P_{\max}$
For current sources: $R = P_{\max}/I^2$
- C : Suitable capacitor
For control gear intended to drive the LED module which includes a logic circuitry
a) for voltage sources: $C = 20 \mu F/A$
b) for current sources: $C = 400 \mu F$
For control gear intended to drive the LED module which does not include a logic circuitry
c) for voltage sources: $C = 1 \mu F/A$
d) for current sources: $C = 1 \mu F$
- LOAD : Equivalent load for the LED module


Figure A.1 – Test circuit for the current when connecting a load

A.3 Measurement of impedance at audio-frequencies (Figure A.2)

The circuit of Figure A.2 illustrates a complete bridge which permits a full determination of the audio-frequency impedance \bar{Z} of the LED module-control gear assembly that is not only its absolute value (modulus) but its variation as well.

Let R' and R'' represent the values of the resistors shown in Figure A.2 by the values of 5Ω and $200 \text{ k}\Omega$ respectively (the latter at least not being critical). When by adjustments of R and C a balance is obtained for a given audio-frequency selected on the wave analyser (or any other suitable selective detector), we have in general:

$$\bar{Z} = R'R''(1/R + j\omega C)$$



IEC 1482/06

U	: supply 50 Hz (60 Hz)
G	: Generator 250 Hz...2 000 Hz
A	: supply transformer 50 Hz (60 Hz)
D.U.T.	: Control gear - LED-module-combination under test
Z_1	: impedance of value sufficiently high for 50 Hz (60 Hz), sufficiently low for 250 Hz to 2 000 Hz (e.g. resistance 15 Ω and capacitance 16 μF)
Z_2	: impedance of value sufficiently low for 50 Hz (60 Hz), sufficiently high for 250 Hz to 2 000 Hz (e.g. inductance 20 mH)
F	: Filter 50 Hz (60 Hz)
W	: Selective voltmeter or wave analyser

NOTE 1 The value of $200 \text{ k}\Omega$ for one branch of the bridge is not critical.

NOTE 2 The impedance Z_1 and/or Z_2 are/is not necessary if the corresponding source has a low impedance for the currents of the other.

Figure A.2 – Measurement of impedance at audio-frequencies

Annex B
(informative)

A guide to quoting product life and failure rate

To allow the lifetime and failure rate of different electronic products to be meaningfully compared by a user it is recommended that the following data be provided by the manufacturer in a product catalogue:

- a) the maximum surface temperature, symbol t_l (t-lifetime) of the electronic product or the maximum part temperature which affects product life, measured under normal operating conditions and at the nominal voltage or at the maximum of the rated voltage range, that allows a life of 50 000 h to be achieved.

NOTE In some countries, such as Japan, a life of 40 000 h should be applied.

- b) the failure rate, if the electronic product is operated continuously at the maximum temperature t_l (defined in a)). Failure rate should be quoted in units of failure in time (fit).

For the method used to obtain the information given in a) and b) above (mathematical analysis, reliability test etc.), the manufacturer should, on request, provide a comprehensive data file containing the details of the method.

www.Lisungroup.com

NORME INTERNATIONALE INTERNATIONAL STANDARD

CEI
IEC
62384

Première édition
First edition
2006-08

**Appareillages électriques alimentés
en courant continu ou alternatif
pour modules de DEL –
Exigences de performances.**

**DC or AC supplied electronic
control gear for LED modules –
Performance requirements**

© IEC 2006 Droits de reproduction réservés — Copyright - all rights reserved

Aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'éditeur.

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

CODE PRIX
PRICE CODE

N

*Pour prix, voir catalogue en vigueur
For price, see current catalogue*

SOMMAIRE

AVANT-PROPOS	4
1 Domaine d'application	8
2 Références normatives	8
3 Termes et définitions	8
4 Notes générales sur les essais	10
5 Classification	10
5.1 Classification en fonction de la charge	10
5.2 Classification en fonction de la tension de sortie	12
5.3 Classification en fonction du courant de sortie	12
6 Marquage	12
6.1 Marquage obligatoire	12
6.2 Marquage optionnel	12
7 Tension et courant de sortie	12
7.1 Exigences au démarrage et à la connexion	12
7.2 Tension et courant en fonctionnement	14
7.3 Exigences pour charges capacitatives	14
7.4 Pics de tension pendant la commutation et le fonctionnement	14
8 Puissance totale du circuit	14
9 Facteur de puissance du circuit	14
10 Courant d'alimentation	14
11 Impédance aux fréquences musicales	16
12 Essais de fonctionnement en conditions anormales	16
13 Endurance	16
Annexe A (normative) Essais	20
Annexe B (informative) Guide pour quantifier la durée de vie et le taux de défaillance	26
Bibliographie	28

CONTENTS

FOREWORD	5
1 Scope	9
2 Normative references	9
3 Terms and definitions	9
4 General notes on tests	11
5 Classification	11
5.1 Classification according to the load	11
5.2 Classification according to the output voltage	13
5.3 Classification according to the output current	13
6 Marking	13
6.1 Mandatory marking	13
6.2 Optional marking	13
7 Output voltage and current	13
7.1 Starting and connecting requirements	13
7.2 Voltage and current during operation	15
7.3 Capacitive load requirement	15
7.4 Voltage surges during switching and operation	15
8 Total circuit power	15
9 Circuit power factor	15
10 Supply current	15
11 Impedance at audio-frequencies	17
12 Operational tests for abnormal conditions	17
13 Endurance	17
Annex A (normative) Tests	21
Annex B (informative) A guide to quoting product life and failure rate	27
Bibliography	29

COMMISSION ÉLECTROTECHNIQUE INTERNATIONALE

APPAREILLAGES ÉLECTRONIQUES ALIMENTÉS EN COURANT CONTINU OU ALTERNATIF POUR MODULES DE DEL – EXIGENCES DE PERFORMANCES

AVANT-PROPOS

- 1) La Commission Electrotechnique Internationale (CEI) est une organisation mondiale de normalisation composée de l'ensemble des comités électrotechniques nationaux (Comités nationaux de la CEI). La CEI a pour objet de favoriser la coopération internationale pour toutes les questions de normalisation dans les domaines de l'électricité et de l'électronique. A cet effet, la CEI – entre autres activités – publie des Normes internationales, des Spécifications techniques, des Rapports techniques, des Spécifications accessibles au public (PAS) et des Guides (ci-après dénommés "Publication(s) de la CEI"). Leur élaboration est confiée à des comités d'études, aux travaux desquels tout Comité national intéressé par le sujet traité peut participer. Les organisations internationales, gouvernementales et non gouvernementales, en liaison avec la CEI, participent également aux travaux. La CEI collabore étroitement avec l'Organisation Internationale de Normalisation (ISO), selon des conditions fixées par accord entre les deux organisations.
- 2) Les décisions ou accords officiels de la CEI concernant les questions techniques représentent, dans la mesure du possible, un accord international sur les sujets étudiés, étant donné que les Comités nationaux de la CEI intéressés sont représentés dans chaque comité d'études.
- 3) Les Publications de la CEI se présentent sous la forme de recommandations internationales et sont agréées comme telles par les Comités nationaux de la CEI. Tous les efforts raisonnables sont entrepris afin que la CEI s'assure de l'exactitude du contenu technique de ses publications; la CEI ne peut pas être tenue responsable de l'éventuelle mauvaise utilisation ou interprétation qui en est faite par un quelconque utilisateur final.
- 4) Dans le but d'encourager l'uniformité internationale, les Comités nationaux de la CEI s'engagent, dans toute la mesure possible, à appliquer de façon transparente les Publications de la CEI dans leurs publications nationales et régionales. Toutes divergences entre toutes Publications de la CEI et toutes publications nationales ou régionales correspondantes doivent être indiquées en termes clairs dans ces dernières.
- 5) La CEI n'a prévu aucune procédure de marquage valant indication d'approbation et n'engage pas sa responsabilité pour les équipements déclarés conformes à une de ses Publications.
- 6) Tous les utilisateurs doivent s'assurer qu'ils sont en possession de la dernière édition de cette publication.
- 7) Aucune responsabilité ne doit être imputée à la CEI, à ses administrateurs, employés, auxiliaires ou mandataires, y compris ses experts particuliers et les membres de ses comités d'études et des Comités nationaux de la CEI, pour tout préjudice causé en cas de dommages corporels et matériels, ou de tout autre dommage de quelque nature que ce soit, directe ou indirecte, ou pour supporter les coûts (y compris les frais de justice) et les dépenses découlant de la publication ou de l'utilisation de cette Publication de la CEI ou de toute autre Publication de la CEI, ou au crédit qui lui est accordé.
- 8) L'attention est attirée sur les références normatives citées dans cette publication. L'utilisation de publications référencées est obligatoire pour une application correcte de la présente publication.
- 9) L'attention est attirée sur le fait que certains des éléments de la présente Publication de la CEI peuvent faire l'objet de droits de propriété intellectuelle ou de droits analogues. La CEI ne saurait être tenue pour responsable de ne pas avoir identifié de tels droits de propriété et de ne pas avoir signalé leur existence.

La Norme internationale CEI 62384 a été établie par le sous-comité 34C: Appareils auxiliaires pour lampes, du comité d'études 34 de la CEI: Lampes et équipements associés

Le texte de cette norme est issu des documents suivants:

FDIS	Rapport de vote
34C/752/FDIS	34C/760/RVD

Le rapport de vote indiqué dans le tableau ci-dessus donne toute information sur le vote ayant abouti à l'approbation de cette norme.

Cette publication a été rédigée selon les Directives ISO/CEI, Partie 2.

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**DC OR AC SUPPLIED ELECTRONIC CONTROL GEAR
FOR LED MODULES –
PERFORMANCE REQUIREMENTS**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62384 has been prepared by subcommittee 34C: Auxiliaries for lamps, of IEC technical committee 34: Lamps and related equipment

The text of this standard is based on the following documents:

FDIS	Report on voting
34/752/FDIS	34/760/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

Cette norme doit être lue conjointement avec la CEI 61347-2-13.

Le comité a décidé que le contenu de cette publication ne sera pas modifié avant la date de maintenance indiquée sur le site web de la CEI sous "http://webstore.iec.ch" dans les données relatives à la publication recherchée. A cette date, la publication sera

- reconduite,
- supprimée,
- remplacée par une édition révisée, ou
- amendée.

www.Lisungroup.cc

This standard is to be read in conjunction with IEC 61347-2-13.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

www.Lisungroup.cc

APPAREILLAGES ÉLECTRONIQUES ALIMENTÉS EN COURANT CONTINU OU ALTERNATIF POUR MODULES DE DEL – EXIGENCES DE PERFORMANCES

1 Domaine d'application

La présente Norme internationale spécifie les exigences de performances relatives aux appareillages électroniques pour utilisation sur des alimentations en courant continu jusqu'à 250 V et sur des alimentations en courant alternatif jusqu'à 1 000 V à 50 Hz ou 60 Hz avec une fréquence de sortie qui peut différer de la fréquence d'alimentation, associés à des modules de DEL conformes à la CEI 62031. Les appareillages pour modules de DEL spécifiés dans cette norme sont conçus pour délivrer une tension ou un courant constants. Cette norme couvre aussi les appareillages qui ne sont pas des générateurs purs de courant ou de tension.

NOTE1 Les essais dans cette norme sont des essais de type. Les exigences applicables aux essais individuels des appareillages en cours de production ne sont pas incluses.

NOTE 2 Les exigences pour les appareillages qui incluent des dispositifs pour la variation de la puissance de sortie sont à l'étude.

NOTE 3 Il y a tout lieu de penser que les appareillages conformes à cette norme assureront un fonctionnement satisfaisant entre 92 % et 106 % de la tension d'alimentation nominale, en prenant en compte les spécifications du fabricant du module de DEL.

2 Références normatives

Les documents de référence suivants sont indispensables pour l'utilisation du présent document. Pour les références datées, seule l'édition citée s'applique. Pour les références non datées, la dernière édition du document de référence s'applique (y compris les éventuels amendements).

CEI 61347-2-13, *Appareillage de lampe – Partie 2-13 Exigences particulières pour les appareillages électroniques alimentés en courant continu ou alternatif pour modules de DEL*

CEI 62031, *Modules de DEL pour l'éclairage général – Exigences de sécurité*¹

DC OR AC SUPPLIED ELECTRONIC CONTROL GEAR FOR LED MODULES – PERFORMANCE REQUIREMENTS

1 Scope

This international standard specifies performance requirements for electronic control gear for use on d.c. supplies up to 250 V and a.c. supplies up to 1 000 V at 50 Hz or 60 Hz with an output frequency which can deviate from the supply frequency, associated with LED modules according to IEC 62031. Control gear for LED modules specified in this standard are designed to provide constant voltage or current. Deviations from the pure voltage and current types do not exclude the gear from this standard.

NOTE 1 The tests in this standard are type tests. Requirements for testing individual control gear during production are not included.

NOTE 2 Requirements for control gear which incorporate means for varying the output power are under consideration.

NOTE 3 It may be expected that control gear complying with this standard will ensure satisfactory operation between 92 % and 106 % of the rated supply voltage, taking into account the specifications of the LED module manufacturer.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61347-2-13, *Lamp controlgear – Part 2-13: Particular requirements for d.c. or a.c. supplied electronic control gear for LED modules*

IEC 62031, *LED modules for general lighting – Safety requirements*¹